

LCR-4070



Features:

- 3½ Digit Display
- 1,999 Count
- Full Protection function, capacitor with the function of Self discharge
- Auto Power Off (APO)

CAPACITANCE

Range	Resolution	Accuracy
200pF	0.1pF	± 2.5% of rdg + 5 digits
2nF	1pF	
20nF	10pF	
200nF	100pF	
2μF	1nF	
20μF	10nF	± 5.0% of rdg + 5 digits
200μF	100nF	
2000μF	1μF	

INDUCTANCE

Range	Resolution	Accuracy
200μH	0.1μH	± 3.0% of rdg + 5 digits
2mH	1μH	± 2.0% of rdg + 5 digits
20mH	10μH	
200mH	100μH	
2H	1mH	± 5.0% of rdg + 5 digits
20H	10mH	

RESISTANCE

Range	Resolution	Accuracy
20Ω	0.01Ω	± 1.0% of rdg + 5 digits
200Ω	0.1Ω	± 0.8% of rdg + 2 digits
2KΩ	1Ω	
20KΩ	10Ω	
200KΩ	100Ω	
20MΩ	10KΩ	± 2.0% of rdg + 5 digits

Special Function

Low Battery Indication	Approx. < 7.5V	Sampling Rate	3 times per second
Capacitance discharge protection	✓	Power	9V(6F22) X 1

- Standard Accessories : Soft Carrying Case, Test Lead, Manual
- Dimension : 185(H) x 93(W) x 35(D)mm