

Features:

- Analog Multimeter with Mirror Scale
- Inbuilt Buzzer and LED
- 0Ω Adjustable with x 100 Range
- Transistor Test, hFE with Diode

DC VOLTAGE

Range	Resolution	Accuracy
0.1mV~1000V	20K Ω /V	3; for 1000V ; 5

DC CURRENT

Range	Resolution	Accuracy
50 μ A~10A	-	3; for 10V ; 5

AC VOLTAGE

Range	Resolution	Accuracy
10V~1000V	9K Ω /V	4; for 1000V ; 5

POWER

AA 1.5V x 2
9V (6F22) x 1

RESISTANCE

Range	Resolution	Accuracy
0.2 Ω ~2k Ω	-	3
2 Ω ~20k Ω		
20 Ω ~200k Ω		
200 Ω ~2M Ω		
2k Ω ~20M Ω		

YX-360 TRE-B



Special Function

Diode Test	✓	Function Protection	✓
Transistor Testing	✓	Continuity Buzzer	About 100 Ω

- Standard Accessories : Test Lead, Manual
- Dimension : 148(H) x 100(W) x 35(D)mm

DM - 830L



Features:

- 3 1/2 Digit Manual Multimeter with Backlight
- 1,999 Count
- Data Hold
- Transistor & Diode Test
- Overload Protection
- Low Battery Indication
- CAT II 600V

DC VOLTAGE

Range	Resolution	Accuracy
200mV	100 μ V	$\pm 0.5\%$ of rdg + 2 digits
2V	1mV	
20V	10mV	
200V	100mV	
600V	1V	$\pm 0.8\%$ of rdg + 2 digits

DC CURRENT

Range	Resolution	Accuracy
200 μ A	0.1 μ A	$\pm 1\%$ of rdg + 2 digits
2mA	1 μ A	
20mA	10 μ A	
200mA	100 μ A	
10A	10mA	$\pm 3\%$ of rdg + 2 digits

AC VOLTAGE

Range	Resolution	Accuracy
200V	100mV	$\pm 1.2\%$ of rdg + 10 digits
600V	1V	

RESISTANCE

Range	Resolution	Accuracy
200 Ω	0.1 Ω	$\pm 0.8\%$ of rdg + 3 digits
2k Ω	1 Ω	$\pm 0.8\%$ of rdg + 2 digits
20k Ω	10 Ω	
200k Ω	100 Ω	$\pm 1.0\%$ of rdg + 2 digits
2M Ω	1K Ω	

POWER

9V (6F22) x 1

TRANSISTOR hFE TEST (0-1000)

Range	Test Range	Test Current	Test Voltage
NPN & PNP	0-1000	1b=10 μ A	Vce=3V

- Standard Accessories : Manual, Test lead
- Dimension : 69(H) x 138(W) x 31(D)mm

